



# Touchkit Software Installation Guide for Windows 2000/XP


Touchkit driver software installation package was created with Installshiled tool. The installation package contains files as below



Double click at the setup.exe file to start software driver installation. Then, the setup program will guide user to complete software installation.




Press **Next** button to continue installation, then, a new dialog popped up as below,




This dialog shows to ask user if the PS2 filter driver for touch screen to be installed. User can check this check for PS2 filter driver installation. The standard PS2 mice can still work well after this filter driver installed because Touchkit PS2 filter driver can work with both standard PS2 mice and PS2 touchscreen. But, this filter driver may does not work with other devices with the PS2 mouse port. After check or uncheck this check box, press **Next** button to continue installation. Then, it shows

new dialog as below,




Also, Touchkit software provides user with a fast 4 points calibration. If the system needs 4 points calibration to make sure the touch accuracy every system reboot, user can check this check box. The 4 points calibration window will be popped up for calibration whenever system boot up if this check box was checked during driver software installation.


Press **Next** button to continue installation. The setup program prompts a message box to hint




user to make sure that the Touchkit USB controller devices were well connected with system USB ports to guarantee the USB touchkit device drivers updated after driver installation. Then, just press **OK** to continue,




A pop up window for user to choose the target path the files will be copied to. Then, Press **Next** to continue,



A dialog popped up for user to assign the target program folder. Press Next




The setup program will scan system COM ports to detect if any Touchkit serial device was connected. If yes, it also pops up a message box for user to make sure if setup program install driver for this new found device.



Just Press **Yes** or **No** to confirm driver installation for this new found device. Finally, if PS2 filter

driver was installed during this software installation, a reboot dialog is popped up for system reboot request to complete driver installation.



After driver installation, a shortcut will be generated and shown on the desktop. And, a new file group generated for Touchkit as below,

